



## Model PSC813 Pressure Transducer for Heavy Industry and General Purpose Industrial Applications

PSC813 Pressure Transducer was developed for all types of industrial applications. The design is based on high temperature, inorganically bonded, media isolated, piezoresistive technology that offers reliable and accurate measurements under harsh environmental conditions. The robust construction of PSC813 offers stable operation when subjected to shock and vibration. Suitable for use in Off-road vehicles, injection molding machines, Hydraulic Pumps and controls, etc.

State of the art design machined from a solid piece of stainless steel provides a leak-proof, all metal sealed system. There are no O-rings, welds or organics exposed to the pressure media. Features digital compensation and temperature correction for high accuracy and stability.

PSC813 offers EMI and RFI immunity as per CE requirements.

- Gauge Pressures
- ASIC Temperature Compensated
- Robust construction to stand high vibrations
- 1.5 % Total Error Band
- Recommended load resistance: >10,000 ohms
- Wetted Parts: 17-4PH SS (other material available)
- Process Fitting: see column Z
- Electrical Connection: DIN43650 connector

### Sample Applications:

- Process Automation & Control
- Plastic and Alloy injection machines
- Test and Measurement Equipment
- Factory Automation
- Energy Management
- Heavy industry



## Model PSC813 Pressure Transducer for Heavy Industry and General Purpose Industrial Applications

Performance (specified @ 25 °C)	
Accuracy (Best fit straight line)	± 0.5% BFSL
Error	± 1.5% FS TEB
Zero/Span Offset Tolerance	± 1.0% FS
Stability (typical)	< ±0.2% full scale per year
Compensated Temperature Range	-20°C~85°C
Operating Temperature Range	-40°C~125°C
Storage Temperature Range	-40°C~125°C
Burst Pressure	4 X Full Scale
Proof Pressure	2 X Full Scale
Pressure Cycles	5 million full scale cycles
Mechanical Vibration	20 g, 10 - 2000 Hz
Mechanical Shock	IEC 60068-2-27, 30 g, 11 ms pulse
Package Protection	IP65 (IEC60529)

### Agency Approvals

IEC61000-4-2	Electrostatic Discharge Immunity: 8kV Contact; 15kV Air; 3 Discharges; Class B. Unit survived
IEC61000-4-3	EM Field Immunity: 50V/m, 1MHz~80MHz; 100V/m, 80MHz~1GHz, 1.0% steps, 2s Dwell. Max recorded output error <±2.0% Span
IEC61000-4-4	Electrical Fast Transient Immunity: 1kV (Level 2), 120s, 5kHz Repetition Rate. Class B. Max recorded output error <±1.5%
IEC61000-4-5	Surge: 1kV (Level 2), L-L 1kV, L-E 2kV. Class B. Max recorded output error <±1.5% Span
IEC61000-4-6	Conducted Immunity: 10V/140dB, 150kHz~80MHz (Level 3). Class B. Max recorded output error <±2.0% Span
IEC61000-4-9	Pulsed Magnetic Field Immunity: 100A/m (Level 3). Class B. Max recorded output error <±1.5% Span
IEC55022 Emission: Class A, 40dB 30-220MHz, 47dB 230MHz-1GHz	



PSC813 Ordering Model NO.: PSC813-X-Y-Z-X			
X	Y	Z	X
Output Type	Pressure Range	Port Type	Special configuration
B = 0.5~4.5V (Ratiometric)	3 = 100 psi 4 = 250 psi	1 = 1/8-27 NPT 2 = 1/4-18 NPT	Consult factory
C = 4~20mA	5 = 500 psi 6 = 1000 psi	3 = DIN3852-A-G1/4 4 = DIN3852-E-G1/4	
D = 1.0~5.0V	7 = 2500 psi 8 = 5000 psi	5 = DIN3852-A-M10*1.0 6 = DIN3852-A-M12*1.5	
E = 0.5~4.5V	9 = 10000 psi	7 = 7/16-20 UNF	
F = 0~10V	A = 15000 psi	X = Special	
G = 0~5V	B = 20000 psi		
X = Special	X = Special		

Electrical data	PSC813-B (Ratiometric)	PSC813-C (4~20mA)	PSC813-D (1.0~5.0VDC)	PSC813-E (0.5~4.5VDC)	PSC813-F (0~10VDC)	PSC813-G (0~5VDC)
Supply Voltage	4.75 ~ 5.25 VDC	9 ~ 32 VDC	8 ~ 32 VDC	8 ~ 32 VDC	12 ~ 32 VDC	8 ~ 32 VDC
Output	0.5 ~ 4.5 VDC	4 ~ 20 mA	1.0 ~ 5.0 VDC	0.5 ~ 4.5 VDC	0 ~ 10 VDC	0 ~ 5 VDC
Supply Current	< 3 mA	< 30 mA	< 3 mA	< 3 mA	< 12 mA	< 3 mA
Zero Output	0.5 VDC	4 mA	1.0 VDC	0.5 VDC	0 VDC	0 VDC
Full Scale Output	4.5 VDC	20 mA	5.0 VDC	4.5 VDC	10 VDC	5 VDC

### Structure reference (Unit: Inch[mm])

